



**M50 Plus**

This dry use vacuum picks up where the others left off. Manufactured to our exacting specifications and sets a new standard of quality durability and value. Ideal for use in any commercial and industrial buildings applications.



**M60 Plus**

When you compare features, reliability and value, this vacuum is the one which all other professional wet/dry vacuums will measure themselves by. Non-tipping tank with five casters will provide you years of dependable service.



**M80 Plus**

The new small giant our Canadian marketplace has been waiting for. It's robust compact design may well be the most dependable value in the market today. Ideal for use in areas where floor space is limited but big enough to handle any dry vacuum application.

Optional tool kits available: **M50 Plus** - MTK2    **M60 Plus** - MTK3    **M80 Plus** - MTK1

MODEL	M50 Plus (dry only)	M60 Plus (wet/dry)	M80 Plus (dry only)
Rated horsepower	1.3	1.6	1.3
Motor type	1-stage flow-thru	2-stage bypass	1-stage flow-thru
Rated amps	8A	10A	8A
Rated volts	120AC	120AC	120AC
Total capacity	27L 5.9 Imp. Gal/7.1 US Gal	27L 5.9 Imp. Gal/7.1 US Gal	22L 4.8 Imp. Gal/5.8 US Gal
Water lift (at closed orifice)	102 inches	104 inches	102 inches
C.F.M. (at tank orifice)	116	105	116
Motor RPM (at full load)	42,300	26,400	42,300
Noise level	69 dB	79.5 dB	69 dB
Hose size	1 1/2" x 8.5'	1 1/2" x 8.5'	1 1/2" x 8.5'
Filter surface area	160	230	160
Cable length	15M	15M	15M
Caster/Wheels	5	5	5
Overall height	28"	28"	26"
Net weight	24 lbs.	26 lbs.	22 lbs.
Shipping weight	26 lbs.	28 lbs.	24 lbs.

*Optional Hepa-type filters are also available upon request*  
10-3-1 years limited warranty on parts and labour

# Procare Plus

Professional Line Wet / Dry Vacuums



**M6012 Plus**

Wet/dry vacuum gives you the same great performance, but with a little more capacity. The non-corrosive tank provides years of dependable service.



**M6018TNP Plus**

Wet/dry vacuum offers even more capacity for those big jobs. With the corrosion resistant injection molded head, the tank won't dent and is resistant to chemical attack.

Tool kit extra: All above vacuums use MTK3

SPECIFICATIONS/MODEL	M6012 Plus (wet/dry)	M6018TNP Plus (wet/dry)
Rated horsepower	1.6	1.6
Motor type	2-stage bypass	2-stage bypass
Rated amps	10A	10A
Rated volts	120AC	120AC
Total capacity	62L 13.7 Imp. Gal/16.4 US Gal	72L 15.9 Imp. Gal/19.0 US Gal
Water lift (at closed orifice)	104 inches	104 inches
C.F.M. (at closed orifice)	105	105
Motor RPM at full load	26,400	26,400
Noise level	79,5dB	79,5 dB
Hose size	1 1/2" x 11.5'	1 1/2" x 11.5'
Filter surface area	562	562
Cable length	15M	15M
Casters/Wheels	4	2 / 2
Overall height	34"	38"
Net weight	45 lbs.	60 lbs.
Shipping weight	48 lbs.	64 lbs.

*Optional Hepa-type filters are also available upon request*  
10-3-1 years limited warranty on parts and labour